LUXE SURFACES

PATTY MADDEN WALLCOVERING

Product Bulletin: Brentwood by Patty Madden

LXB-BWD-01 – Suma
LXB-BWD-02 – Tolo
LXB-BWD-03 – Bango
LXB-BWD-04 – Bamboo
LXB-BWD-05 – Lauma
LXB-BWD-06 – Baltic
LXB-BWD-07 – Safari
LXB-BWD-08 – Congo
LXB-BWD-09 – Kapok
LXB-BWD-10 – Acacia
LXB-BWD-11 – Ramon
LXB-BWD-12 – Musa
LXB-BWD-13 – Grove
LXB-BWD-14 – Rattan
LXB- BWD-15 – Kauri
LXB-BWD-16 – Asha
LXB-BWD-17 – Kaiko
LXB-BWD-18 – Bloom

The Inspiration: Woven Woodland Geometry

The Aesthetic: Brentwood by Patty Madden draws its inspiration from the quiet geometry of wood and the rhythmic handwork of raffia weaving. Broad horizontal bands of earthen fibre - natural strips - are "woven" into a richly worked surface. Subtle changes in tone and tactile embossing soften the pattern's linear structure, balancing architectural order with the expressive irregularity of handcraft. Earthy yet refined, Brentwood brings a biophilic warmth to contemporary interiors—a woven landscape where woodland character and artisan detail share the same rhythm.

Product Specifications:

- Type II performance wallcovering
- Weight: 20 oz. per LY/ 619 g per LM
- Width: 52–54 inches / 1.32–1.37 m
- Backing: Non-woven
- Repeat: Random
- Install: Reverse hang / Random match
- Tensile strength: ASTM D 4034
- Tear strength: ASTM D 2261
- Seam slippage: ASTM D 4034
- Material sold in 30 LY bolts
- VOC: meets CA 01350
- Mildew resistance / Anti-microbial
- Exceeds G.S.A. CCC-W-408D for Type II materials; tested to CCC-T-191-B
- Contains bactericides and mildew inhibitors to discourage mold and mildew under normal conditions
- Class A fire-rated – ASTM E84
- Flame spread: 25; Smoke density factor: 15
- 5-year warranty against manufacturer defects