

## Vergence 3D Color Wood



### Physical Properties

Content: 20 oz. Mylar wallcovering (Textured Emboss)

Mylar Backing: Non-woven

Width: 52"

Install Info: Straight; non-reversible

### Performance

Fire Rating: Class A ASTM E84

Flame Spread: Class A PASS

Smoke Developed: Class A PASS

Meets or exceeds all requirements of Federal

Specification CCC-W-408 A/B/C/D

Tensile Strength: 50 x 55

Tear Strength: 25 x 25

Color fastness to light: 200 hours / BS782 (UK) PASS

Surface Resistance: PASS

Abrasion Resistance: PASS

Cleaning: Soft rag with water or gentle detergent. Do not scrub or use abrasives.

**NOTE\*** The assigned numerical reading & other tests referenced here are not intended to reflect hazards presented by this or any other material under actual fire conditions. Consult an architect or fire safety engineer for information on applicable building codes & reduction of fire hazards, including the use of sprinklers.

### Sustainability

Printed with UV-curable inks that produce high image quality, improve productivity = time & cost savings. UV-curable printing may reduce the environmental impact of printing relative to solvent-based printing.

**Manufactured in the USA**

**luxesurfaces**

© 2020 Luxe Surfaces  
All Rights Reserved